

VALVE	MAIN	WEIGHT			
SIZE	L±1.5	øW	H (APP.)	'T'	IN Kg. (APPROX.)
15mm	60	60	94	1/2"	0.480
20mm	70	60	97	3/4"	0.660

10	SCREW/BOLT	1	M.S.	BS 936
9	WASHER	1	M.S.	BS 936
8	HANDWHEEL	1	C.I./ STEEL	IS 210 Gr. FG 200/
7	STEM	1	H.T.BRASS	FHTB 1 OF IS:6912
6	GLAND NUT	1	G.M.	LTB2 OF IS:318
5	GLAND	1	G.M.	LTB2 OF IS:318
4	GLAND PACKING	-	ASBETOS	IS:4687
3	BONNET	1	G.M.	LTB2 OF IS:318
2	DISC	1	G.M.	LTB2 OF IS:318
1	BODY	1	G.M.	LTB2 OF IS:318
PART No.	PART NAME	No. OFF	MATERIAL	REMARKS

PART	REVISION	REV.	DATE	APPD.	REMARK	
No.		No.		BY		
						TITLE
						SCAL
						N.T.S
						IN. I.
						lФr
						Ψ,
TELK						

MILTON OVERSEAS

TLE :- C.M. GLODE WALKER OF A	ALL DIMESNSIONS IN MM			
G.M. GLOBE VALVE CL-I	UNLESS OTHERWISE SPECIFIED			
ISI MARKED, SCREWED IN BONNET,	DRN.	N.S.PAL	24.04.10	
INTEGRAL SEAT RING, RISING STEM,	CHKD.		24.04.10	
FLANGED ENDS PRODUCT SPECIFICATION :- IS:778:84	APPD.			
CALE TEST PRESSURE :-	DRG. No. :-			
T.S. BODY :- 1.5 Mpa. (HYD.)	301-SDF-10-G-D-CM			
SEAT :- 1.0 Mpg. (HYD.)	ISSUE STATUS 00			
MAX. WORKING PRESSURE :- 1.0 Mpa. AT 45°C	SHEET	1 OF 1		